

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)
[First Hit](#)

☐ [Generate Collection](#)

L19: Entry 3 of 10

File: DWPI

Mar 15, 1979

DERWENT-ACC-NO: 1979-C4944B
DERWENT-WEEK: 197912
COPYRIGHT 2004 DERWENT INFORMATION LTD

TITLE: Eddy current displacement transducer - has AC fed coils adjacent layers of high conductivity and low permeability material

INVENTOR: NUERNBERGE, W

PATENT-ASSIGNEE:

ASSIGNEE

CODE

SIEMENS AG

SIEI

PRIORITY-DATA: 1977DE-2739054 (August 30, 1977)

[Search Selected](#)[Search ALL](#)[Clear](#)

PATENT-FAMILY:

	PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
<input type="checkbox"/>	DE 2739054 A	March 15, 1979		000	
<input type="checkbox"/>	DE 2739054 C	October 28, 1982		000	

INT-CL (IPC): G01B 7/02; G01D 5/14

ABSTRACTED-PUB-NO: DE 2739054A
BASIC-ABSTRACT:

A probe member (1) is subjected to small displacements (s1, s2) by applied forces (K1, K2). Attached to the probe are transducer elements (2) of a conductive, relatively low permeability material such as stainless steel. Closely spaced to the transducer elements (of the order of 10-1 - 10-2 mm) is the rear surface of AC fed induction coils (3), the outer surfaces of which are embedded in an isolating potting compound (6).

A metallic screen (5) surrounds the device. The relative permeability of the transducer element is in the range $1 < \mu_r < 10$ and the frequency of the AC supply to the induction coils is given by $2(\pi)f\mu_r(\sigma) = \text{const.}$ where f is the frequency and (σ) is the conductivity of the transducer material. The relative permeability is typically about 3.

TITLE-TERMS: EDDY CURRENT DISPLACEMENT TRANSDUCER AC FEED COIL ADJACENT LAYER HIGH CONDUCTING LOW PERMEABLE MATERIAL

DERWENT-CLASS: S02

BEST AVAILABLE COPY

[Previous Doc](#)

[Next Doc](#)

[Go to Doc#](#)